

AIPHONE

DB Series



Hands-free Two-Wire Electric Lock Door Phone



Audio Door Entry You Can Count

Easy to install and simple to use, the DB Series protects private homes. For an ideal audio door entry solution, use Aiphone's DB Series !

Only 27mm




Hands-Free Communication in Any Place

With the DB Series' compact design, it can fit anywhere in your home. Convenient hands-free communication is convenient for anyone to use.




Up to 5 Inside Stations With Room-to-Room Communication

Unable to answer your door from the Master station? No problem! Talk with visitors from anywhere in your home with up to 4 additional Sub master stations. Inside stations can be used for room-to-room communication.




Call multiple inside stations at the same time for room-to-room communication.



Option Button

Use the Option button to control an external device, such as an entrance light.



Chime Sound

Just a press of the Call button of Door station rings the chime continuously for appropriate time (approximately 4 seconds).




On

and apartments.

2-Wire System for Simple Installation


With the easy to install two-wire system, use the DB Series to replace your door bell.




System Configuration



For Private Homes



For Apartment Blocks



DB Series

Line up



DA-1DS
Door station silver panel




DA-2DS
2-Call door station



DA-4DS
4-Call door station



DB-1MD
Master station



DB-1SD
Sub master station



PT-1211DR
AC transformer
(Input: AC230V)



PT-1211C
AC transformer
(Input: AC120V)



PT-1211D
AC transformer
(Input: AC230V)



IER-2
Call extension



EL-12S
Electric door strike




TAR-3
External signaling relay



AC-10S
Vandal resistant
access control keypad,
surface mount



AC-10F
Vandal resistant
access control keypad,
flush mount



DAW-P
Door station
mounting plate
(83.5mm)











Boxed set



DBS-1AP :
DB-1MD, DA-1DS, PT-1211DR

DBS-1A :
DB-1MD, DA-1DS, PT-1211C or PT-1211D

Unit dimensions(mm)



Features


- Two-wire system including door release
- Door release wired to door station, requiring no power transformer
- Total hands-free communication, auto-voice actuation
- Press-to-talk operation available
- User-optional function button
- Call tone MUTE with indicator
- Call extension sounder

Specifications

Power source	15V AC
AC transformer	PT-1211DR, PT-1211C, PT-1211D
Communication	Approx. 1 min. AUTOMATIC (Hands-free); To activate, momentarily press TALK button. MANUAL (Press-to-talk/Release-to-listen); To activate, press TALK button for 1 sec. or more.
Door release	EL-12S or others (More than (AC) 70Ω AC 9.5 ~ 20V)
Option contact (AC/DC)	Voltage Max. : 24V, Min. : 1V Current Max. : 1.6A, Min. : 10mA
Wiring	2 wires, throughout AC trans - Master - Door - Door release
Distance	PT-1211DR/C/D ~ Door rlse. 110m(0.65mmØ) 200m(0.8mmØ) 310m(1.0mmØ) PT-1211DR/C/D ~ DB-1MD 55m(0.65mmØ) 100m(0.8mmØ) 155m(1.0mmØ) DB-1MD ~ farthest DB-1SD 100m(0.65 ~ 1.0mmØ)

Caution

When existing chime wires are used, it is possible they contain AC voltage. Electric shock or unit damage could result. Ask a qualified electrician for more details.



Distributed by :



Deming Medal



ISO 9001 Certified
JQA-0291
AIPHONE CO., LTD.



ISO 14001 Certified
JQA-EM0453
Headquarters section
Toyota Factory
Taiho Site
AIPHONE CO., LTD.

AIPHONE®
Providing Peace of Mind
<http://www.aiphone.net/>

DB(E)0809A

All rights reserved. All statements valid at time of printing. The design and specifications are subject to change without notice for improvement.

Printed in Japan (E)
MA52004AYZ